

# DMP 331



## Industrial Pressure Transmitter for Low Pressure

### Stainless Steel Sensor

**accuracy according to IEC 60770:**  
 standard: 0.35 % FSO  
 option: 0.25 / 0.1 % FSO

**DMP 331** Industrial Pressure Transmitter

**Nominal pressure**

from 0 ... 100 mbar  
 up to 0 ... 40 bar

**Output signals**

2-wire: 4 ... 20 mA  
 3-wire: 0 ... 20 mA / 0 ... 10 V  
 others on request

**Special characteristics**

- ▶ perfect thermal behaviour
- ▶ excellent long term stability
- ▶ **pressure port**  
**G 1/2" flush from 100 mbar on**

**Optional versions**

- ▶ IS-version  
 Ex ia = intrinsically safe for gases and dusts
- ▶ SIL 2  
 according to IEC 61508 / IEC 61511
- ▶ **pressure sensor welded**
- ▶ customer specific versions

The pressure transmitter DMP 331 can be used in all industrial areas when the medium is compatible with stainless steel 1.4404 (316 L) or 1.4435 (316 L). Additional are different elastomer seals as well as a helium tested welded version available.

The modulare concept of the device allows to combine different stainless steel sensors and electronic modules with a variety of electrical and mechanical versions.

Thus a diversity of variations is created, meeting almost all requirements in industrial applications.

**Preferred areas of use are**



Plant and Machine Engineering



Environmental Engineering  
 (water - sewage - recycling)



Energy Industry



Input pressure range									
Nominal pressure gauge / abs.	[bar]	-1...0	0.10	0.16	0.25	0.40	0.60	1	1.6
Overpressure	[bar]	5	0.5	1	1	2	5	5	10
Burst pressure $\geq$	[bar]	7.5	1.5	1.5	1.5	3	7.5	7.5	15
Nominal pressure gauge / abs.	[bar]	2.5	4	6	10	16	25	40	
Overpressure	[bar]	10	20	40	40	80	80	105	
Burst pressure $\geq$	[bar]	15	25	50	50	120	120	210	
Vacuum resistance		$P_N \geq 1$ bar: unlimited vacuum resistance $P_N < 1$ bar: on request							

Output signal / Supply	
Standard	2-wire: 4 ... 20 mA / $V_s = 8 \dots 32 V_{DC}$
Option IS-protection	2-wire: 4 ... 20 mA / $V_s = 10 \dots 28 V_{DC}$
Options 3-wire	3-wire: 0 ... 20 mA / $V_s = 14 \dots 30 V_{DC}$ 0 ... 10 V / $V_s = 14 \dots 30 V_{DC}$

Performance	
Accuracy <sup>1</sup>	standard: nominal pressure < 0.4 bar: $\leq \pm 0.5$ % FSO nominal pressure $\geq 0.4$ bar: $\leq \pm 0.35$ % FSO option 1: nominal pressure $\geq 0.4$ bar: $\leq \pm 0.25$ % FSO option 2: for all nominal pressure: $\leq \pm 0.1$ % FSO
Permissible load	current 2-wire: $R_{max} = [(V_s - V_s \text{ min}) / 0.02] \Omega$ current 3-wire: $R_{max} = 500 \Omega$ voltage 3-wire: $R_{min} = 10 \text{ k}\Omega$
Influence effects	supply: 0.05 % FSO / 10 V <span style="float:right">load: 0.05 % FSO / k<math>\Omega</math></span>
Long term stability	$\leq \pm 0.1$ % FSO / year at reference conditions
Response time	2-wire: $\leq 10$ msec <span style="float:right">3-wire: <math>\leq 3</math> msec</span>

<sup>1</sup> accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability)

Thermal effects (Offset and Span)			
Nominal pressure $P_N$	[bar]	-1 ... 0	$< 0.40$ <span style="float:right"><math>\geq 0.40</math></span>
Tolerance band	[% FSO]	$\leq \pm 0.75$	$\leq \pm 1$ <span style="float:right"><math>\leq \pm 0.75</math></span>
in compensated range	[°C]	-20 ... 85	0 ... 70 <span style="float:right">-20 ... 85</span>

Permissible temperatures	
Permissible temperatures	medium: -40 ... 125 °C electronics / environment: -40 ... 85 °C storage: -40 ... 100 °C

Electrical protection	
Short-circuit protection	permanent
Reverse polarity protection	no damage, but also no function
Electromagnetic compatibility	emission and immunity according to EN 61326

Mechanical stability	
Vibration	10 g RMS (25 ... 2000 Hz) according to DIN EN 60068-2-6
Shock	500 g / 1 msec according to DIN EN 60068-2-27


Materials	
Pressure port	stainless steel 1.4404 (316 L)
Housing	stainless steel 1.4404 (316 L)
Option compact field housing	stainless steel 1.4305 (303), cable gland brass, nickel plated <span style="float:right">others on request</span>
Seals (media wetted)	standard: FKM options: EPDM NBR welded version <sup>2</sup> <span style="float:right">others on request</span>
Diaphragm	stainless steel 1.4435 (316 L)
Media wetted parts	pressure port, seals, diaphragm

<sup>2</sup> welded version only with pressure ports according to EN 837

Explosion protection (only for 4 ... 20 mA / 2-wire)	
Approval DX19-DMP 331	IExU 10 ATEX 1068 X zone 0: II 1G Ex ia IIC T4 Ga zone 20: II 1D Ex ta IIIC T 85°C, IP6x <b>in preparation</b>
Safety technical maximum values	$U_i = 28$ V, $I_i = 93$ mA, $P_i = 660$ mW, $C_i \approx 0$ nF, $L_i \approx 0$ $\mu$ H
Permissible temperatures for environment	in zone 0: -20 ... 60 °C with $p_{atm}$ 0.8 bar up to 1.1 bar in zone 1 or higher: -20 ... 70 °C
Connecting cables (by factory)	cable capacitance: signal line/shield also signal line/signal line: 160 pF/m cable inductance: signal line/shield also signal line/signal line: 1 $\mu$ H/m

<b>Miscellaneous</b>	
Option SIL 2	according to IEC 61508 / IEC 61511
Current consumption	signal output current: max. 25 mA      signal output voltage: max. 5 mA
Weight	approx. 140 g
Installation position	any <sup>3</sup>
Operational life	> 100 x 10 <sup>6</sup> pressure cycles
CE-conformity	EMC Directive: 2004/108/EC


<sup>3</sup> Pressure transmitters are calibrated in a vertical position with the pressure connection down. If this position is changed on installation there can be slight deviations in the zero point for pressure ranges  $P_N \leq 1$  bar.



**Pin configuration**

Electrical connection	ISO 4400	Binder 723 (5-pin)	M12x1 / metal (4-pin)	field housing	cable colours (DIN 47100)
Supply +	1	3	1	IN +	wh (white)
Supply -	2	4	2	IN -	bn (brown)
Signal + (for 3-wire)	3	1	3	OUT+	gn (green)
Shield	ground pin	5	4	⏏	gn/ye (green / yellow)

**Electrical connections (dimensions in mm)**




⇒ universal field housing stainless steel 1.4404 (316 L) with cable gland M20x1.5 (ordering code 880) and other versions on request

<sup>4</sup> standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70°C)

<sup>5</sup> different cable types and lengths available, permissible temperature depends on kind of cable


**Mechanical connections (dimensions in mm)**

**standard for accuracy 0.35 / 0.25 %**




G1/2" DIN 3852  
with ISO 4400

**standard for accuracy 0.1 %;  
SIL- and SIL-IS-version**




G1/2" DIN 3852  
with ISO 4400


**option**




G1/2" EN 837




G1/2" open port




G1/2" DIN 3852  
with flush sensor




G1/4" DIN 3852



G1/4" EN 837



1/2" NPT



1/4" NPT

⇨ **metric threads and other versions on request**

This data sheet contains product specification, properties are not guaranteed. Subject to change without notice.

